

VI. CONCLUSION

Attribute reduction is an important application on data analysis in rough set theory. The paper studies the attribute reduction based on discernibility matrix combining the dependence of decision attribute on condition attribute in incomplete table and presents a new attribute reduction algorithm based on incomplete decision table, which improves the two aspects of time and space complexity. Finally, the algorithm is proved to be effective by experiments.

REFERENCES

- [1] Pawlak Z. Rough sets [J]. International Journal of Computer and Information Science, 1982, 11(5):341-356.
- [2] Pawlak Z, Skowron A. Rough set: Some extensions[J]. Information Science. 2007, 177 :41-73.
- [3] Zhang weixu, Wu zhiwei, Liang jiye. Theories and Methods of Rough Set [M], Science Press, 2001.
- [4] Wang guoyin, Zhang qinghua. Uncertainty of Rough Sets in Different Knowledge Granularities [J], Chinese Journal of Computers, 2008,31(9):1588-1598.
- [5] Shu wenhao, Xu zhangyan, Qian wenbin, Yang bingru. Quick Attribute Reduction Algorithm Based Incomplete Decision Table [J], Chinese Journal of Computers, 2011,32(9),1867-1871.
- [6] Teng shuhua, Zhou shilin, Sun jixiang, Li zhiyong. Attribute Reduction Algorithm Based on Conditional Entropy under Incomplete Information System[J]. Journal of National University of Defense Technology, 2010, 32(1), 90-94.
- [7] Li xiukai, Shi kaiquan. A Knowledge Granulation-based Algorithm for Attribute Reduction under Incomplete Information Systems[J]. Compute Sciences, 2006, 33(11), 169-170.
- [8] Ge hao, Li longshu, Yang chuanjian. Discernibility Matrix Based on Credibility and Attribute Reduction Method[J]. Journal of Sichuan University (Engineering Science Edition), 2011, 43(5), 146-152.
- [9] Kryszkiewicz M. Rough set approach to incomplete information systems [J]. Information Sciences, 1998, 112(1):39-49.